

Smooth, pellicular coating for **LUCEM Choc** microcement inside

- Excellent adhesion on **LUCEM Choc**
- Suitable for floors, walls, walk-in showers and furniture
- Excellent final strength
- Polished concrete finish
- Easy application

PRESENTATION



Colored paste

DILUTION

N/A

COVERAGE



0.15 to 0.20 kg / m²

MATERIAL



Planeo spatula, STR

COLORS



90 colors from the color chart

CONDITIONS OF USE



Room and product temperatures :
5 à 30°C

▲ Out of this range the aesthetic and mechanical properties of the product and its adhesion to the substrate may be reduced.

DRYING TIME



Before the sealant, the water-oil repellent or the wax	8 hours*
Before placing furniture	7 days
Before laying the carpet	15 days

* Indications to be adapted depending on the temperature, humidity and ventilation of the room.

CLEANING THE TOOLS



With water before the product has dried.

PREPARATION OF THE SURFACE

The **LUCEMChoc®** microcement must be dry (moisture should stand at less than 5%), sanded and the dust removed.

① Base coat sealer

Apply one coat of **AD LUCEM** base coat sealer. Refer to the *base coat sealer data sheet for instructions*.

▲ Not allowing the product to dry properly could lead aesthetic defects (traces, lighter color, ghosts, etc.).

APPLICATION

APPLICATION

① LUCEMLiss®

Apply one thin layer of **LUCEMLiss®** with Planeo spatula and burnish it to get rid of the imperfections. Do not apply thick.

② Sanding

When dry, lightly sand the surface with a 120 grit abrasive and remove dust with a vacuum cleaner.

SPECIFIC PRECAUTIONS


Read the safety information specification on the internet www.adlucem-matieres.com for proper use and waste disposal information.

FINISHING COAT

SEALANT/ WAX

The smoothing mortar **LUCEMLiss®** should be protected with **AD LUCEM** sealant or wax. Refer to *technical sheets for the instructions*.

PACKAGING



STORAGE

STORAGE

Store away from frost and from important heat.

SHELF-LIFE

1 year in original packaging